



1D & 2D



Duo Near &



IP65



drop



## **Features**

## **Duo Scanning Technology.**

The EX90 is designed with advanced Duo technology, which combines two independent scan engines working in tandem to provide efficient near-far barcode scanning. By using two separate scan engines, the EX90 can quickly and seamlessly switch between them based on the distance of the barcode, resulting in faster scanning and improved productivity.

## Compatible Design.

The pistol grip is compatible with MT90 Orca III and allows for easy attachment to the device, while its lightweight and well-balanced design reduces stress and fatigue during long work sessions.

## Long-range Reading Ability.

The EX90 is able to read 1D and 2D barcodes at a distance of up to 9.8 meters.

## Industrial Durability.

Featuring an IP65 sealing, the EX90 is protected against water and dust and withstands 1.2m drops to concrete.

## Long Battery Life.

The MT90 III is equipped with a 4500mAh battery that supports the EX90 for up to 12 hours on a single charge.

## Suggested industries











Warehousing

# EX90 Pistol Grip Duo Near & Far Technical specifications

### **Data Capture**

White LED Illumination Laser aiming **Aiming** 1280x800, monochrome, 30 frame/sec Resolution Up to 30f/s self-adaption Scan Rate 75mm-2600mm Depth of Field Code128 (15mil) 440mm-9800mm Depth of Field Code128 (100mil) 190mm-310mm Depth of Field DataMatrix (10mil) 105mm-3900mm Depth of Field DataMatrix (55mil) 195mm-250mm Depth of Field QR Code (10mil) 110mm-3700mm Depth of Field QR (55mil) **Performance** Pitch 75°, Skew 45° Scan Angle **Physical** 160(W) x 82(D) x 165(H) mm Dimensions (mm) 230g Weight Trigger on pistol grip User Input

### **Environmental**

Operating Temperature -20°C to 50°C (-4°F to 122°F)

Storage Temperature -30°C to 70°C (-22°F to 158°F)

Humidity 5% to 95% (non-condensing)

Electro Static Discharge (ESD) ±15kV (air discharge), ±8kV (direct discharge)

Drop 1.2m

IP Rating IP65

## Communication

Host Terminal MT90 Orca III

Host Connection 8-pin connector



+31 (0) 345 87 00 33

info@newland-id.com

newland-id.com

Feel free to contact us or a partner near you

visit newland-id.com/partners

Specifications are subject to change without notice

© Newland EMEA 2022, all rights reserved

